


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 600/60 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	587	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1685	<b>RIM ALT</b>	DW 18 L
<b>SLR (MM)</b>	757	<b>ECE</b>	E11-106R-006414
<b>RC (MM)</b>	5077	<b>SRI</b>	800

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2345	2705	3110	3465	3875	4230	4740	5095
<b>FROM 65 TO 40</b>	2580	2970	3420	3810	4260	4650	5210	5600
30	2630	3030	3485	3885	4340	4740	5315	5710
20	2680	3085	3555	3960	4425	4835	5415	5820
10	2835	3265	3760	4190	4685	5115	5730	6160
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	3610	4160	4785	5335	5960	6510	7295	7840
10 HT	2630	3030	3485	3885	4340	4740	5315	5710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.