

# TF 8181

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 7.50 - 16                              |
| <b>UM</b>           | IS STANDARD                            |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                 |
| <b>MACHINERY</b>    | TRATTORE 2WD / TRATTORE /<br>RIMORCHIO |
| <b>VERSIONE</b>     | SPECIAL                                |
| <b>TIRE TYPE</b>    | TT                                     |
| <b>LI/SS</b>        | 98 A6                                  |



## DIMENSIONI IS STANDARD

|                 |      |                |                     |
|-----------------|------|----------------|---------------------|
| <b>SW (MM)</b>  | 205  | <b>RIM REC</b> | 5.50 F              |
| <b>OD (MM)</b>  | 820  | <b>RIM ALT</b> | 5.00 F; 5 K; 6.00 F |
| <b>SLR (MM)</b> | 383  | <b>ECE</b>     | E11-106R-004412     |
| <b>RC (MM)</b>  | 2445 | <b>PR</b>      | 6                   |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.80</b> |
| 30                | 750         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.