


# RIDEMAX IT 697 (M+S)

<b>TIRE SIZE</b>	<b>480/65 R 28 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	149 D ; 154 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94062720	<b>RC (IN)</b>	160.9
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	DW 15 L
<b>OD (IN)</b>	52.6	<b>RIM ALT</b>	DW 14 L; DW 16 L
<b>SLR (IN)</b>	24.2	<b>ECE</b>	E11-106R-006159

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
40	3370	4160	4870	5670	6380	7160
30	3640	4490	5260	6120	6890	7740
25	3890	4790	5620	6450	7360	8270
20	4050	4980	5840	6790	7650	8600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.