

FLOTATION 648

TIRE SIZE	600/50 - 22.5
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	DUAL BEAD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	156 A8/152 B
LI/SS FREE ROLLING	169 A8/165 B



DIMENSÕES IS STANDARD

SW (MM)	611	RIM REC	AG 20.00
OD (MM)	1170	ECE	E11-106R-004392
SLR (MM)	510	PR	20
RC (MM)	3501		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.00	3.10	3.20
10 FR	7820	7975	8120
20 FR	7035	7175	7310
30 FR	6255	6380	6495
40 FR	5585	5695	5800
50 FR	5025	5125	5150
10 DW	5390	5495	5600
20 DW	4850	4945	5040
30 DW	4310	4395	4480
40 DW	3850	3925	4000
50 DW	3465	3535	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.