

FLOTATION TR 675

TIRE SIZE	500/60 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊗ BIAS
MACHINERY	IMPLEMENTOS AGRÍCOLAS / REBOQUE / IMPLEMENTOS AGRÍCOLAS
VERSÃO	DUAL BEAD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	155 A8/151 B
LI/SS FREE ROLLING	168 A8/164 B



DIMENSÕES IS STANDARD

SW (MM)	515	RIM REC	AG 16.00
OD (MM)	1181	RIM ALT	15.00; 17.00
SLR (MM)	542	ECE	E11-106R-004395
RC (MM)	3604	PR	20

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70	3.80	4.00
10 FR	7425	7545	7840
20 FR	6685	6790	7055
30 FR	5940	6035	6270
40 FR	5305	5390	5600
50 FR	4775	4850	5000
10 DW	5255	5340	5425
20 DW	4730	4805	4885
30 DW	4205	4275	4340
40 DW	3755	3815	3875
50 DW	3380	3435	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.