

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	167 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	DW 16 L ; W 16 A ; DD 16
<b>OD (MM)</b>	1951	<b>RIM ALT</b>	DW 18 A ; DD 18 ; W 18 A ; DD 18 L
<b>SLR (MM)</b>	858	<b>ECE</b>	E4-106R-001491
<b>RC (MM)</b>	5782	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.4	2.8	3.2
50	2270	2640	3015	3385	3755	4125	4635	5070	5450
40	2270	2640	3015	3385	3755	4125	4635	5070	5450
30	2430	2830	3225	3625	4020	4415	4960	5425	5830
10 LT	3045	3540	4040	4535	5035	5530	6210	6795	7305
10 HT	2430	2830	3225	3625	4020	4415	4960	5425	5830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.