


# AW 702

<b>TIRE SIZE</b>	<b>6.00 - 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / REMORCĂ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	95 A8



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	169	<b>RIM REC</b>	4.00 E
<b>OD (MM)</b>	722	<b>RIM ALT</b>	4.50 E; 4½ K
<b>SLR (MM)</b>	334	<b>ECE</b>	E4-106R-001958
<b>RC (MM)</b>	2197	<b>PR</b>	6

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.75</b>
10 FR	965
25 FR	820
30 FR	775
40 FR	690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.