DATA SHEET

PRINTED ON
23-04-2026

AGRIMAX ELOS

TYRE SIZE	**480/70 R 34**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	155 A8 ; 155 B

DIMENSIONS IS STANDARD

SW (MM)	500	**RIM REC**	W 15 L
OD (MM)	1605	**RIM ALT**	W 16 L; W 14 L
SLR (MM)	733	**ECE**	E11-106R-007532
RC (MM)	4868	**SRI**	750

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	1515	1785	2055	2290	2560	2790	3065	3375	3645	3875
40	1515	1785	2055	2290	2560	2790	3065	3375	3645	3875
30	1620	1910	2200	2450	2740	2990	3280	3615	3905	4150
10 LT	2030	2390	2755	3070	3430	3745	4105	4520	4885	5195
10 HT	1620	1910	2200	2450	2740	2990	3280	3615	3905	4150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..