


EARTHMAX SR 23

| | |
|---------------------|--|
| TIRE SIZE | 20.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | NIVELEUSE / CHARGEUR |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 161 A8 ; 186 A2 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|-----------|--------------------|-------|
| OD (MM) | 1490 | TRA CODE | G2/L2 |
| SLR (MM) | 668 | STAR RATING | ★ |
| RC (MM) | 4489 | | |
| RIM REC | 17.00/2.0 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.25 | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 40 | 2430 | 2800 | 3150 | 3450 | 3875 | 4125 | 4375 | 4625 | --- | -- | -- | -- | -- |
| 10 | -- | -- | -- | -- | -- | -- | -- | -- | 8000 | 8250 | 8750 | 9000 | 9500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.