


# AGRIMAXFACTOR

<b>TYRE SIZE</b>	<b>360/70 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	125 D ; 128 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	357	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	1255	<b>RIM ALT</b>	W 10 ; W 12
<b>SLR (MM)</b>	577	<b>ECE</b>	E11-106R-0010947
<b>RC (MM)</b>	3747	<b>SRI</b>	600

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	910	1060	1205	1355	1505	1650
50	955	1115	1270	1425	1580	1735
40	1000	1160	1325	1485	1650	1800
30	1045	1220	1390	1560	1730	1900
10 LT	1220	1420	1620	1820	2020	2215
10HT	1045	1220	1390	1560	1730	1900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.