

## BK 6060



# BK 6060



BK 6060 is a both field- and road-oriented tyre for trailers and backhoe loaders in transport as well as digging and loading applications. This block pattern tyre provides an extended tyre life-cycle.



| SIZE | TT/TL     | PR | LI/SS | RIM                                                                                |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION |
|------|-----------|----|-------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|---------|
|      |           |    |       | REC<br>RIM                                                                         | ALT<br>RIM                                                                         |              |            |             |            |         |
|      |           |    |       |  |  |              |            |             |            |         |
| Ø16" | 9.00 - 16 | TT | 16    | -                                                                                  | 6.50 H                                                                             | 6.00 G       | 925        | 432         | 2847       | IND     |

IND: INDUSTRIAL

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   | -                                                                                   | -                                                                                   |

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index