

# FLOTATION 648

<b>TIRE SIZE</b>	<b>850/50 - 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDÉUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	168 A8/164 B
<b>LI/SS FREE ROLLING</b>	180 A8/176 B



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94006571	<b>RC (IN)</b>	194.3
<b>SW (IN)</b>	33.5	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	65.0	<b>ECE</b>	E11-106R-004564
<b>SLR (IN)</b>	28.0	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	16	19	22
5 FR	20600	22720	24690
10 FR	18540	20450	22220
20 FR	16480	18180	19750
25 FR	14720	16230	17640
30 FR	13250	14600	15650
5 DW	14420	15890	17280
10 DW	12970	14310	15550
20 DW	11530	12720	13820
25 DW	10300	11350	12350
30 DW	9270	10220	11020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.