


EARTHMAX SR 475

| | |
|---------------------|--|
| TIRE SIZE | 24.00 R 35 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | САМОСВАЛ С ЖЕСТКОЙ РАМОЙ |
| VERSION | STANDARD COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 209 B |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|--------------------|-----------|
| USA CODE | 94066940 | RIM REC | 17.00/3.5 |
| OD (IN) | 85.0 | TRA CODE | E4 |
| SLR (IN) | 38.2 | STAR RATING | ★★ |
| RC (IN) | 259.4 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 30900 | 32000 | 34200 | 35300 | 36400 | 37500 | 38600 | 39700 | 40800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.