

CRANE SPECIAL



CRANE SPECIAL



CRANE SPECIAL is suitable for pick & carry cranes on rough terrains. The tire is made of a special compound which provides high stability and durability.



	SIZE	US CODE	TT/TL	PR	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
						REC RIM	ALT RIM					
												
Ø24"	14.00 - 24	94041282	TL	24	-	10.00 W	-	14.8	53.9	24.7	159.4	STD
	14.00 - 24	94043934	TT	24	-	10.00 W	-	14.8	53.9	24.7	159.4	STD
Ø25"	18.00 - 25	94041213	TL	32	-	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	STD
	16.00 - 25	94040582	TL	28	-	11.25/2.0	-	18.2	58.5	26.9	173.0	STD
	16.00 - 25	94041541	TT	28	-	11.25/2.0	-	18.2	58.5	26.9	173.0	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index	