


# AGRIMAX SIRIO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>540/65 R 38</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | HOCHLEISTUNGSTRAKTOR / TRACTOR   |
| <b>VERSION</b>      | HIGH SPEED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 153 D ; 150 E  |



## ABMESSUNGEN IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 530  | <b>RIM REC</b> | W 16 L         |
| <b>OD (MM)</b>  | 1667 | <b>RIM ALT</b> | W 18 L         |
| <b>SLR (MM)</b> | 769  | <b>ECE</b>     | E4-106R-000816 |
| <b>RC (MM)</b>  | 5050 | <b>SRI</b>     | 800            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 70         | 1575 | 1810 | 2080 | 2345 | 2615 | 2885 | 3120 | 3350 |
| 65         | 1720 | 1975 | 2265 | 2555 | 2850 | 3140 | 3395 | 3650 |
| 50         | 1805 | 2075 | 2380 | 2685 | 2995 | 3300 | 3570 | 3835 |
| 40         | 1880 | 2160 | 2480 | 2800 | 3120 | 3440 | 3720 | 4000 |
| 25         | 2040 | 2340 | 2685 | 3035 | 3380 | 3725 | 4030 | 4330 |
| 10         | 2575 | 2960 | 3395 | 3835 | 4275 | 4710 | 5095 | 5475 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.