


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	710/50 R 30.5
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKBIL / SLÄPVAGN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D

## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	272	<b>RIM REC</b>	AG 24.00
<b>OD (MM)</b>	1485	<b>RIM ALT</b>	AG 20.00
<b>SLR (MM)</b>	676	<b>ECE</b>	E4-106R-001498
<b>RC (MM)</b>	4533	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2220	2520	3060	3540	4080	4620	4980	5520	6000
65	2405	2730	3315	3835	4420	5005	5395	5980	6500
50	2915	3305	4015	4645	5350	6060	6530	7240	7865
40	3275	3715	4510	5220	6015	6810	7340	8135	8840
25	3805	4315	5240	6060	6985	7910	8525	9450	10270
10	4330	4915	5970	6905	7960	9010	9715	10765	11700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.