


# RIB 774 (A)

<b>TIRE SIZE</b>	<b>18X8.50 - 8</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SLÄPVAGN / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	85 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94056910	<b>RC (IN)</b>	54.7
<b>SW (IN)</b>	8.9	<b>RIM REC</b>	7.00   - 55 ;   - 70 ;   - 90
<b>OD (IN)</b>	18.1	<b>ECE</b>	E11-106R-004622
<b>SLR (IN)</b>	8.5	<b>PR</b>	6

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>44</b>
<b>5 FR</b>	1590
<b>15 FR</b>	1360
<b>20 FR</b>	1270
<b>25 FR</b>	1140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.