


AGRIMAX RT 765

420/70 R 24

| | |
|--------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ILAÇLAMA / TRAKTÖR / ÜZÜM HASAT MAKINESİ / BIÇERDÖVER / UYGULAMALI MAKİNE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| | 130 D |



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 418 | RIM REC | W 13 |
| OD (MM) | 1248 | RIM ALT | W 12; W 14 L |
| SLR (MM) | 554 | ECE | E11-106R-005826 |
| RC (MM) | 3680 | SRI | 600 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 1045 | 1220 | 1390 | 1560 | 1730 | 1900 |
| 50 | 1100 | 1280 | 1460 | 1640 | 1820 | 1995 |
| 40 | 1150 | 1335 | 1525 | 1710 | 1900 | 2085 |
| 30 | 1205 | 1400 | 1600 | 1795 | 1990 | 2185 |
| 10 LT | 1405 | 1635 | 1865 | 2095 | 2325 | 2550 |
| 10 HT | 1205 | 1400 | 1600 | 1795 | 1990 | 2185 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.