


# RIDEMAX FL 693 M

<b>TIRE SIZE</b>	<b>600/55 R 26.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI
<b>VERSIONE</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	177 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1333	<b>ECE</b>	E11-106R-003007
<b>SLR (MM)</b>	586	<b>SRI</b>	625
<b>RC (MM)</b>	4077		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
65	2265	2705	3285	3800	4380	4965	5330	5915	6500	6865	7300
50	2740	3270	3980	4595	5305	6010	6450	7160	7865	8305	8835
40	3080	3675	4470	5165	5960	6755	7250	8045	8840	9335	9930
30	3420	4080	4965	5735	6615	7500	8050	8935	9815	10365	11025
25	3580	4270	5195	6000	6925	7845	8425	9345	10270	10845	11535
10	4075	4865	5915	6835	7885	8940	9595	10645	11695	12355	13140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.