


EARTHMAX SR 22



| | |
|---------------------|--|
| TIRE SIZE | 17.5 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PLANIERER / RADLADER / PLANIERER / RADLADER / PLANIERER / PLANIERER |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 153 A8 ; 176 A2 |

ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|--------------------|-----------|
| USA-CODE | 94044092 | RIM REC | 14.00/1.5 |
| OD (IN) | 53.1 | TRA CODE | G2/L2 |
| SLR (IN) | 23.2 | STAR RATING | ★ |
| RC (IN) | 155.5 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 18 | 22 | 25 | 29 | 33 | 36 | 40 | 44 | 58 | 62 | 65 | 69 | 73 |
|-----------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 25 | 4080 | 4680 | 5200 | 5840 | 6400 | 6800 | 7400 | 8050 | - | - | - | - | - |
| 5 | - | - | - | - | - | - | - | - | 13200 | 13600 | 14300 | 14800 | 15700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.