


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 750/70 R 44</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	186 D

## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	760	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	2175	<b>RIM ALT</b>	DW 24 B
<b>SLR (MM)</b>	958	<b>ECE</b>	E11-106R-006765
<b>RC (MM)</b>	6450	<b>SRI</b>	1025

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2
70	4325	5015	5710	6485	7180	7870	8645
<b>FROM 65 TO 40</b>	4750	5510	6270	7125	7885	8645	9500
30	4845	5625	6400	7270	8045	8820	9690
20	4940	5735	6525	7410	8205	8995	9880
10	5225	6065	6900	7840	8675	9510	10450
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	6650	7715	8780	9975	11040	12105	13300
10HT	4845	5625	6400	7270	8045	8820	9690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.