


AGRIMAX TERIS

| | |
|---------------------|------------------------------------------------------------------------------------------|
| TIRE SIZE | 710/55 R 28 CHO |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ERNTEMASCHINE / BAUMWOLLERNTEMASCHINE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 164 A8/B |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 716 | RIM REC | DW 23 B |
| OD (MM) | 1493 | ECE | E11-106R-005940 |
| SLR (MM) | 663 | SRI | 700 |
| RC (MM) | 4442 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1950 | 2250 | 2550 | 2900 | 3200 | 3550 | 3950 | 4250 | 4650 | 5000 |
| 40 | 1950 | 2250 | 2550 | 2900 | 3200 | 3550 | 3950 | 4250 | 4650 | 5000 |
| 30 | 2090 | 2410 | 2730 | 3105 | 3425 | 3800 | 4230 | 4550 | 4980 | 5350 |
| 15 CYC | 3220 | 3715 | 4210 | 4785 | 5280 | 5860 | 6520 | 7015 | 7675 | 8250 |
| 10 CYC | 3510 | 4050 | 4590 | 5220 | 5760 | 6390 | 7110 | 7650 | 8370 | 9000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.