



PRINTED ON  
22-04-2026

## DATA SHEET

# SM 55 L5S

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>18.00 - 25</b>                                      |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  |
| <b>MACHINERY</b>    | UNDERGROUND MINING VEHICLE /<br>LOW PROFILE DUMP TRUCK |
| <b>VERSION</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |



### DIMENSIONS US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA CODE</b> | 94044696 | <b>RIM REC</b>  | 13.00/2.5 |
| <b>OD (IN)</b>  | 65.6     | <b>RIM ALT</b>  | 15.00/2.5 |
| <b>SLR (IN)</b> | 30.1     | <b>PR</b>       | 40        |
| <b>RC (IN)</b>  | 201.5    | <b>TRA CODE</b> | L5S       |

### LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>138</b> |
| 5                | 37500      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.