


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>320/70 R 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	123 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94021932	<b>RC (IN)</b>	115.7
<b>SW (IN)</b>	12.6	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	38.7	<b>RIM ALT</b>	W 9 ; W 11
<b>SLR (IN)</b>	17.5	<b>ECE</b>	E4-106R-000644

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>30</b>	1610	1850	2130	2390	2670	2940	3190	3420
<b>25</b>	1610	1850	2130	2390	2670	2940	3190	3420
<b>20</b>	1730	1980	2270	2570	2850	3150	3410	3660
<b>5 LT</b>	2160	2480	2840	3220	3580	3950	4270	4590
<b>5 HT</b>	1730	1980	2270	2570	2850	3150	3410	3660

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.