


# AGRIMAX RT 945

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>320/90 R 54</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | FELDSPRITZE / TRACTOR /<br>LANDWIRTSCHAFTLICHE GERÄTE                                    |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 156 A8/B   |



## ABMESSUNGEN US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA-CODE</b> | 94037094 | <b>RC (IN)</b> | 237.0           |
| <b>SW (IN)</b>  | 12.6     | <b>RIM REC</b> | W 10            |
| <b>OD (IN)</b>  | 76.7     | <b>RIM ALT</b> | W 9; W 11       |
| <b>SLR (IN)</b> | 36.6     | <b>ECE</b>     | E11-106R-003474 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52    | 58    | 64    | 70    |
|-----------|------|------|------|------|------|------|------|-------|-------|-------|-------|
| 30        | 3310 | 4270 | 5160 | 5720 | 6040 | 6600 | 7160 | 7650  | 8050  | 8820  | -     |
| 25        | 3310 | 4270 | 5160 | 5720 | 6040 | 6600 | 7160 | 7650  | 8050  | 8820  | -     |
| 20        | 3540 | 4570 | 5520 | 6130 | 6470 | 7080 | 7670 | 8190  | 8620  | 9440  | -     |
| 5         | -    | 4100 | 5160 | 6350 | 7540 | 8730 | 8990 | 10050 | 11110 | 12170 | 13230 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.