

# AS 504

<b>TIRE SIZE</b>	<b>400/80 - 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	INDUSTRIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	156 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	394	<b>RIM REC</b>	W 13
<b>OD (MM)</b>	1262	<b>RIM ALT</b>	W 12; W 14 L
<b>SLR (MM)</b>	566	<b>SRI</b>	600
<b>RC (MM)</b>	3655		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.80
10	5000
25	4240
30	4160
40	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.