

# TR 882

<b>TIRE SIZE</b>	<b>400/60 - 15.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	BALER / HAY HARVESTER / IMPLEMENT MACHINERY / TRAILER / HARVESTER / IMPLEMENTS / TRAILER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	137 A8
<b>LI/SS FREE ROLLING</b>	149 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	400	<b>RIM REC</b>	AG 13.00
<b>OD (MM)</b>	875	<b>ECE</b>	E4-106R-001878
<b>SLR (MM)</b>	378	<b>PR</b>	18
<b>RC (MM)</b>	2605	<b>SRI</b>	410

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>4.50</b>
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250
10 DW	3220
25 DW	2735
30 DW	2575
40 DW	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.