


FL 630 SUPER

| | |
|---------------------|--|
| TIRE SIZE | 600/55 R 26.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ÉPANDEUR / VÉHICULE CITERNE / REMORQUE / OUTILLAGE AGRICOLE |
| VERSION | HD |
| TIRE TYPE | TL |
| LI/SS | 177 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| CODE USA | 94048946 | RC (IN) | 161.6 |
| SW (IN) | 24.1 | RIM REC | AG 20.00 |
| OD (IN) | 52.5 | ECE | E11-106R-003005 |
| SLR (IN) | 23.8 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 73 | 87 |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40 | 4020 | 4990 | 5960 | 7240 | 8380 | 9660 | 10950 | 11750 | 13040 | 14330 | 15130 | 16090 |
| 30 | 4870 | 6040 | 7210 | 8770 | 10130 | 11690 | 13250 | 14220 | 15780 | 17340 | 18310 | 19480 |
| 25 | 5480 | 6790 | 8100 | 9850 | 11390 | 13140 | 14890 | 15980 | 17740 | 19490 | 20580 | 21890 |
| 20 | 6080 | 7540 | 8990 | 10950 | 12640 | 14580 | 16530 | 17750 | 19700 | 21640 | 22850 | 24300 |
| 15 | 6360 | 7890 | 9410 | 11450 | 12320 | 15270 | 17290 | 18570 | 20600 | 22640 | 23910 | 25430 |
| 5 | 7240 | 8980 | 10720 | 13040 | 15070 | 17380 | 19710 | 21150 | 23470 | 25780 | 27240 | 28970 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.