

# AS 504

<b>TIRE SIZE</b>	<b>15.5/80 - 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	151 A8
<b>LI/SS FREE ROLLING</b>	163 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94019007	<b>RC (IN)</b>	152.6
<b>SW (IN)</b>	15.1	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	49.7	<b>RIM ALT</b>	W 13; W 14 L
<b>SLR (IN)</b>	22.4	<b>ECE</b>	E4-106R-002265

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58
5 FR	15050
15 FR	12790
20 FR	12040
25 FR	10750
5 DW	10650
15 DW	9050
20 DW	8520
25 DW	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.