


AGRIMAX RT 945

| | |
|---------------------|--|
| TYRE SIZE | 320/90 R 46 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 148 D ; 151 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94051694 | RC (IN) | 206.0 |
| SW (IN) | 12.6 | RIM REC | W 10 |
| OD (IN) | 68.7 | RIM ALT | W 9 ; W 11 |
| SLR (IN) | 31.9 | ECE | E11-106R-004068 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 |
|-----------|------|------|------|------|------|------|------|-------|
| 40 | 2990 | 3890 | 4730 | 5210 | 5490 | 6050 | 6540 | 6940 |
| 30 | 3140 | 4090 | 4970 | 5480 | 5760 | 6350 | 6870 | 7300 |
| 25 | 3270 | 4270 | 5180 | 5710 | 6020 | 6620 | 7150 | 7610 |
| 20 | 3440 | 4480 | 5430 | 5990 | 6300 | 6940 | 7510 | 7980 |
| 5 | 4490 | 5840 | 7090 | 7810 | 8230 | 9070 | 9800 | 10420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.