



PRINTED ON  
23-04-2026

## DATA SHEET

# LOADER PLUS

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>14.00 - 25</b>                                    |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | HJULLASTARE / BULLDOZER /<br>HJULLASTARE / BULLDOZER |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |



### DIMENSIONER US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA CODE</b> | 94064915 | <b>RIM REC</b>  | 10.00/1.5 |
| <b>OD (IN)</b>  | 53.9     | <b>PR</b>       | 20        |
| <b>SLR (IN)</b> | 24.8     | <b>TRA CODE</b> | L3        |
| <b>RC (IN)</b>  | 159.4    |                 |           |

### LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>102</b> |
| 5                | 18700      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.