

# LG 306

|                     |                    |
|---------------------|--------------------|
| <b>TYRE SIZE</b>    | <b>18X8.50 - 8</b> |
| <b>UM</b>           | IS STANDARD        |
| <b>CONSTRUCTION</b> | ⊠ BIAS             |
| <b>MACHINERY</b>    | TRACTOR            |
| <b>VERSION</b>      | STANDARD           |
| <b>TYRE TYPE</b>    | TL                 |



## DIMENSIONS IS STANDARD

|                 |      |                |                             |
|-----------------|------|----------------|-----------------------------|
| <b>SW (MM)</b>  | 215  | <b>RIM REC</b> | 7.00   - 55;   - 70;   - 90 |
| <b>OD (MM)</b>  | 450  | <b>ECE</b>     | E11-106R-003448             |
| <b>SLR (MM)</b> | 204  | <b>PR</b>      | 4                           |
| <b>RC (MM)</b>  | 1346 |                |                             |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>1.50</b> |
| 15                | 375         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.