


AGRIMAXFACTOR

| | |
|---------------------|--|
| TIRE SIZE | 360/70 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 125 D ; 128 A8 |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA CODE | 94513673 | RC (IN) | 147.5 |
| SW (IN) | 14.1 | RIM REC | W 11 |
| OD (IN) | 49.4 | RIM ALT | W 10 ; W 12 |
| SLR (IN) | 22.7 | ECE | E11-106R-0010947 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 40 | 2010 | 2340 | 2660 | 2990 | 3320 | 3640 |
| 30 | 2110 | 2460 | 2800 | 3140 | 3480 | 3820 |
| 25 | 2200 | 2560 | 2920 | 3270 | 3640 | 3990 |
| 15 | 2300 | 2690 | 3060 | 3440 | 3810 | 4190 |
| 5 LT | 2690 | 3130 | 3570 | 4010 | 4450 | 4880 |
| 5 HT | 2300 | 2690 | 3060 | 3440 | 3810 | 4190 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.