

# FLOTATION 558

<b>TIRE SIZE</b>	500/45 - 22.5
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALER / HAY HARVESTER / TANKER / TRAILER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	ARAMID BELTED HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	142 A8/138 B
<b>LI/SS FREE ROLLING</b>	154 A8/150 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94048281	<b>RC (IN)</b>	124.7
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	41.1	<b>ECE</b>	E11-106R-005352
<b>SLR (IN)</b>	18.5	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	46	49	52
5 FR	10800	11190	11570
10 FR	9720	10070	10420
20 FR	8640	8950	9260
25 FR	7720	7990	8270
30 FR	6940	7200	7390
5 DW	7640	7910	8180
10 DW	6880	7120	7360
20 DW	6110	6340	6550
25 DW	5460	5650	5840
30 DW	4920	5090	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.