


# FL 630 SUPER

<b>TIRE SIZE</b>	<b>600/55 R 26.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPREADER / TANKER / TRAILER / IMPLEMENTS
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	165 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1333	<b>ECE</b>	E4-106R-001414
<b>SLR (MM)</b>	606	<b>SRI</b>	625
<b>RC (MM)</b>	4078		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1505	1740	1970	2395	2770	3190	3615	3895	4315	4690
65	1650	1910	2165	2630	3040	3505	3970	4275	4740	5150
50	2000	2310	2620	3180	3680	4240	4805	5180	5740	6235
40	2245	2595	2945	3575	4135	4765	5395	5815	6445	7005
25	2605	3015	3420	4155	4805	5540	6270	6760	7490	8140
10	2970	3435	3895	4730	5470	6305	7140	7695	8530	9270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.