


AGRIMAX RT 600



TIRE SIZE	900/60 R 32
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HARVESTER / SPREADER / TRACTOR / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	181 A8 ; 178 B

DIMENSIONS IS STANDARD

SW (MM)	896	RIM REC	DW 27 B
OD (MM)	1893	RIM ALT	DW 28 B ; DW 30 B
SLR (MM)	841	ECE	E11-106R-005768
RC (MM)	5697	SRI	900

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	3375	3825	4350	4800	5325	5925	6375	6975	7500	-	-
40	3715	4210	4785	5280	5860	6520	7015	7675	8250	-	-
30	3975	4505	5125	5655	6270	6980	7510	8215	8830	-	-
10 LT	4975	5640	6415	7080	7850	8735	9400	10285	11055	-	-
10 HT	3975	4505	5125	5655	6270	6980	7510	8215	8830	-	-
10 CYC.	-	6765	7690	8485	9415	10475	11270	12330	13255	13465	14025

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.