


# SM 55 L5S

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 26.5 - 25  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | VEICOLO PER MINIERE SOTTERRANEE<br>/ DUMPER DI BASSO PROFILO                           |
| <b>VERSIONE</b>     | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSIONI IS STANDARD

|                 |           |                 |     |
|-----------------|-----------|-----------------|-----|
| <b>OD (MM)</b>  | 1798      | <b>PR</b>       | 28  |
| <b>SLR (MM)</b> | 816       | <b>TRA CODE</b> | L5S |
| <b>RC (MM)</b>  | 5322      |                 |     |
| <b>RIM REC</b>  | 22.00/3.0 |                 |     |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.75</b> |
| 10                | 15500       |
| 15                | 13485       |
| 25                | 12400       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.