


# RIDEMAX IT 696

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>400/80 R 28 IND</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 151 A8 ; 146 D   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94039227 | <b>RC (IN)</b> | 159.4          |
| <b>SW (IN)</b>  | 15.9     | <b>RIM REC</b> | W 13           |
| <b>OD (IN)</b>  | 53.2     | <b>RIM ALT</b> | W 12 ; W 14 L  |
| <b>SLR (IN)</b> | 24.2     | <b>ECE</b>     | E4-106R-002401 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 17   | 23   | 29   | 35   | 41   | 46   |
|-----------|------|------|------|------|------|------|
| 40        | 3110 | 3840 | 4500 | 5220 | 5890 | 6610 |
| 30        | 3370 | 4170 | 4880 | 5680 | 6390 | 7190 |
| 25        | 3570 | 4410 | 5170 | 6010 | 6770 | 7610 |
| 20        | 3730 | 4610 | 5400 | 6270 | 7070 | 7940 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.