

# MP 567

|                     |   |
|---------------------|---|
| <b>TYRE SIZE</b>    | 12.5 - 20   |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | IMPLEMENT MACHINERY /<br>IMPLEMENTS / UNIVERSAL VEHICLE |
| <b>VERSION</b>      | HD  |
| <b>TYRE TYPE</b>    | TL  |



## DIMENSIONS US STANDARD

|                 |          |                |        |
|-----------------|----------|----------------|--------|
| <b>USA CODE</b> | 94060207 | <b>RC (IN)</b> | 123.7  |
| <b>SW (IN)</b>  | 12.8     | <b>RIM REC</b> | 11.0   |
| <b>OD (IN)</b>  | 40.9     | <b>RIM ALT</b> | 12 SDC |
| <b>SLR (IN)</b> | 19.3     | <b>PR</b>      | 12     |

## LOAD CAPACITY (LBS/TYRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>51</b> |
| 55               | 4410      |
| 25               | 5070      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.