


# AS 504

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | 7.5L - 15  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS |
| <b>MACHINERY</b>          | TELEHANDLER / FIELD TRAILER /<br>IMPLEMENTS / TELEHANDLER                              |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TT   |
| <b>LI/SS DRIVE WHEEL</b>  | 100 A8   |
| <b>LI/SS FREE ROLLING</b> | 113 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 210  | <b>RIM REC</b> | 6 LB            |
| <b>OD (MM)</b>  | 765  | <b>RIM ALT</b> | 5 K; 5½ J; 5½ K |
| <b>SLR (MM)</b> | 354  | <b>ECE</b>     | E4-106R-002632  |
| <b>RC (MM)</b>  | 2280 | <b>PR</b>      | 8               |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.70 |
|------------|------|
| 10 FR      | 1610 |
| 25 FR      | 1370 |
| 30 FR      | 1290 |
| 40 FR      | 1150 |
| 10 DW      | 1120 |
| 25 DW      | 950  |
| 30 DW      | 895  |
| 40 DW      | 800  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.