

# FLOTATION 648

<b>TIRE SIZE</b>	<b>850/50 - 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALER / HAY HARVESTER / SPREADER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	176 A8/173 B
<b>LI/SS FREE ROLLING</b>	189 A8/185 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94030286	<b>RC (IN)</b>	194.3
<b>SW (IN)</b>	33.5	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	65.0	<b>ECE</b>	E11-106R-004566
<b>SLR (IN)</b>	28.0	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33	34	36
5 FR	30280	31030	31790
10 FR	27250	27930	28610
20 FR	24220	24820	25430
25 FR	21630	22170	22710
30 FR	19470	19950	20390
5 DW	20870	21380	21910
10 DW	18780	19250	19720
20 DW	16690	17110	17530
25 DW	14900	15280	15650
30 DW	13410	13750	14330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.