


# TR 315

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>23X10.50 - 12</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |  BIAS                                  |
| <b>MACHINERY</b>    | LANDWIRTSCHAFTLICHE GERÄTE /<br>ERNTEMASCHINE FÜR OBST /<br>GRABENFRÄSE / ERNTEMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |



## ABMESSUNGEN IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 255  | <b>RIM REC</b> | 8½ JA           |
| <b>OD (MM)</b>  | 600  | <b>RIM ALT</b> | 7 JA            |
| <b>SLR (MM)</b> | 272  | <b>ECE</b>     | E11-106R-005206 |
| <b>RC (MM)</b>  | 1840 | <b>PR</b>      | 10              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.80</b> |
| 15                | 1100        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.