


AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 11.0/65 - 12 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 101 A8 |
| LI/SS FREE ROLLING | 114 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94019434 | RC (IN) | 81.6 |
| SW (IN) | 10.7 | RIM REC | 9.00 |
| OD (IN) | 27.6 | ECE | E4-106R-002834 |
| SLR (IN) | 12.6 | PR | 8 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 42 |
|-----------|------|
| 5 FR | 3640 |
| 15 FR | 3100 |
| 20 FR | 2910 |
| 25 FR | 2600 |
| 5 DW | 2550 |
| 15 DW | 2160 |
| 20 DW | 2040 |
| 25 DW | 1820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.