

# TRAC GRADER +

|                     |                   |
|---------------------|-------------------|
| <b>TIRE SIZE</b>    | <b>14.00 - 24</b> |
| <b>UM</b>           | IS STANDARD       |
| <b>CONSTRUCTION</b> |                   |
| <b>MACHINERY</b>    | GRADER            |
| <b>VERSION</b>      | STANDARD          |
| <b>TIRE TYPE</b>    | TL                |



## DIMENSIONS IS STANDARD

|                 |             |                 |  |
|-----------------|-------------|-----------------|--|
| <b>OD (MM)</b>  | 1348        | <b>RIM ALT</b>  | 9.00/1.5 (DC); 10.00 VA SDC;<br>10.00 WA SDC |
| <b>SLR (MM)</b> | 598         | <b>PR</b>       | 12   |
| <b>RC (MM)</b>  | 3990        | <b>TRA CODE</b> | G2   |
| <b>RIM REC</b>  | 8.00 TG SDC |                 |  |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.50</b> |
| 40                | 3075        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.