


AGRIMAX PROHARVEST

TIRE SIZE	VF 1020/55 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ERNTEMASCHINE
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	200 D



ABMESSUNGEN IS STANDARD

SW (MM)	1010	ECE	E11-106R-0011309
OD (MM)	2060	SRI	975
RC (MM)	57		
RIM REC	36.00 VA (multi-piece)		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8	3.2
70	4970	5735	6500	7390	8155	9050	10065	10195	11850	12740
FROM 65 TO 40	5460	6300	7140	8120	8960	9940	11060	11200	13020	14000
30	5570	6430	7285	8285	9140	10140	11285	11425	13285	14280
20	5680	6555	7430	8445	9320	10340	11505	11650	13545	14560
10	6010	6930	7855	8935	9860	10935	12170	12320	14325	15400
*UPTO 30 CYC	6200	7155	8105	9220	10170	11285	12555	12715	14780	15890
*UPTO 15 CYC	7400	8540	9675	11005	12145	13470	14990	15180	17645	18970
*UPTO 10 CYC	8110	9360	10605	12060	13310	14765	16425	16635	19335	20790
10HT	5570	6430	7285	8285	9140	10140	11285	11425	13285	14280

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.