

AGRIMAX FORCE

TIRE SIZE	IF 600/70 R 30 CFO
UM	IS STANDARD
MACHINERY	HARVESTER / HIGH-POWER TRACTOR / TRACTOR
VERSION	SPECIAL
TL/TT	TL
LI/SS	165 D

DIMENSIONS IS STANDARD

SW (MM)	603	RIM REC	DW 21 B ; DW 21 A
OD (MM)	1602	RIM ALT	DW 20 A ; DW 20 B
SLR (MM)	708	ECE	E11-106R-006495
RC (MM)	4800	SRI	750

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2200	2525	2900	3280	3650	4025	4400	4685
FROM 65 TO 40	2420	2780	3190	3605	4015	4425	4840	5150
30	2515	2890	3315	3745	4175	4600	5030	5355
20	2610	3000	3445	3890	4335	4775	5225	5560
10	3070	3530	4050	4575	5095	5615	6145	6540
UPTO 30 CYC	3145	3610	4145	4685	5215	5750	6290	6695
UPTO 15 CYC	3750	4305	4940	5585	6220	6855	7500	7980
UPTO 10 CYC	4110	4725	5420	6125	6825	7520	8225	8755
10 HT	2515	2890	3315	3745	4175	4600	5030	5355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

