

# BK 826

|                     |                                |
|---------------------|--------------------------------|
| <b>TYRE SIZE</b>    | 9.00 - 16                      |
| <b>UM</b>           | IS STANDARD                    |
| <b>CONSTRUCTION</b> | ❖ BIAS                         |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS / TRAILER |
| <b>VERSION</b>      | TRACTOR TRAILER                |
| <b>TYRE TYPE</b>    | TT                             |
| <b>LI/SS</b>        | 138 A6                         |



## DIMENSIONS IS STANDARD

|                |        |            |                 |
|----------------|--------|------------|-----------------|
| <b>SW (MM)</b> | 265    | <b>ECE</b> | E11-106R-005356 |
| <b>OD (MM)</b> | 925    | <b>PR</b>  | 18              |
| <b>RIM REC</b> | 6.50 H |            |                 |
| <b>RIM ALT</b> | 6.00 G |            |                 |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>7.60</b> |
| 30                | 2360        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.