

# FL 630 SUPER

<b>TIRE SIZE</b>	<b>580/65 R 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	РАЗБРАСЫВАТЕЛЬ / АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	174 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	582	<b>RIM REC</b>	AG 18.00
<b>OD (MM)</b>	1326	<b>RIM ALT</b>	AG 16.00; AG 17.00; AG 20.00
<b>SLR (MM)</b>	594	<b>ECE</b>	E11-106R-008289
<b>RC (MM)</b>	4058	<b>SRI</b>	625

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
70	1955	2440	2745	3175	3600	3965	4335	4760	5065	5370	5735	6100
65	2145	2680	3015	3485	3955	4355	4760	5230	5565	5900	6300	6700
50	2600	3245	3650	4220	4785	5275	5760	6330	6735	7140	7625	8110
40	2920	3650	4105	4740	5380	5925	6475	7110	7570	8025	8570	9115
25	3390	4240	4770	5510	6250	6885	7520	8265	8790	9320	9955	10590
10	3860	4825	5430	6275	7120	7840	8565	9410	10010	10615	11340	12060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.