

# AS 504

**12.5/80 - 18****UM** IS STANDARD**CONSTRUCTION**  BIAS**MACHINERY** TELESKOPIK YÜKLEYİCİ / TARLA  
RÖMORKU / UYGULAMALI MAKİNE /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

135 A8

148 A8



## UNDEFINED IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 308  | <b>RIM REC</b> | W 9             |
| <b>OD (MM)</b>  | 987  | <b>RIM ALT</b> | 9; 11           |
| <b>SLR (MM)</b> | 438  | <b>ECE</b>     | E11-106R-004347 |
| <b>RC (MM)</b>  | 2892 | <b>PR</b>      | 16              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.90 |
|------------|------|
| 10 FR      | 4410 |
| 25 FR      | 3750 |
| 30 FR      | 3530 |
| 40 FR      | 3150 |
| 10 DW      | 3050 |
| 25 DW      | 2595 |
| 30 DW      | 2440 |
| 40 DW      | 2180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.