

AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 340/85 R 24 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 125 A8/B |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 353 | RIM REC | W 12 |
| OD (MM) | 1188 | RIM ALT | W 11 |
| SLR (MM) | 531 | ECE | E4-106R-000604 |
| RC (MM) | 3540 | SRI | 575 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 910 | 1060 | 1205 | 1355 | 1505 | 1650 |
| 40 | 910 | 1060 | 1205 | 1355 | 1505 | 1650 |
| 30 | 975 | 1135 | 1295 | 1455 | 1615 | 1770 |
| 10 LT | 1220 | 1420 | 1620 | 1820 | 2020 | 2215 |
| 10 HT | 975 | 1135 | 1295 | 1455 | 1615 | 1770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.